



Document code	B02
Revision code	01
Revision date	20.11.2014
Publication date	22.07.2014
Page no	1

SLAUGHTERING CONVEYOR



USAGE AREA: 1ST CLASS SLAUGHTER HOUSES

QUALITY: ST 37 , GALVANIZED BODY

PROPERTIES OF MACHINE

A- SUBJECT:

Providing slaughtering conveyor for using in the slaughter hall of slaughter houses.

B- TECHNICAL PROPERTIES

- Body of the bovine slaughtering conveyors will be steel casting after the slaughtering hook is processed properly, electro-galvanize will be applied.
- Ç 1040 material will be used in pulley and surface of pulley will be processed onto pipe with balance and will be electro-galvanized and will be bearing pulley from both side.
- Spindle of the pulley will be produced from Ç 1040 material and will be immobilized to the main body with one side wedged cotter pin.
- 2 piece of 6201 ZZ immobilized roller will take part in the pulley. Rollers will have carrying capacity of at least 1000 kg in their middle part.
- There will be a calibrated chain on the lower part of the body for taking animals on rail by tying them from their legs. Chain length will not be less than 1400 mm and size will be 8*28 mm. Hot-dip galvanism will be processed.
- Spool pin will be electro-galvanized after it is processed with respect to center of roller
- Pipe type will be hook for monorail.

C. GENERAL ISSUES

- Will be appropriate to the matters which is signified on Technical Properties.
- 2 years of warranty will be provided for slaughtering conveyor.