



Document code	K01
Revision code	01
Revision date	20.11.2014
Publication date	22.07.2014
Page no	1

SHEEP SLAUGHTERING ELEVATOR



USAGE AREA: 1ST CLASS SLAUGHTER HOUSES

QUALITY: ST 37, GALVANIZED BODY

PROPERTIES OF MACHINE

A-SUBJECT:

Providing quartering elevator for using in the slaughter hall of slaughter houses.

B- TECHNICAL PROPERTIES:

- With the help of pushing boots on the sheep slaughtering elevator at interval of 1000 mm sheep will be transferred alive to slaughtering twinrail with the angle of nearly 45 degree.
- Sheep slaughtering elevator is in the power of 2 HP and will be provoked with worm gear
- One of the chain wheel provide the movement with the help of other chain wheel in the engine reducer.
- Other wheel is stretch forming and will be mounted to the tail part of the sachet.
- Bedding of wheels to the sachets will be bearing.
- On the elevator slaughtering elevator will be mounted to twinrail and on the tail part it will be mounted to the ground with special pins.
- Body will be hot-dip galvanized but wheels and chain will be electro-galvanized
- Sheep slaughtering elevator will be mounted with whole equipment and panel and electric connections will be done and delivered in running mode.

C. GENERAL ISSUES

- Will be appropriate to the matters which is signified on Technical Properties.
- 2 years of warranty will be provided for sheep slaughtering elevator.